



Beauty without sacrifice!

Segezha Art.
Plywood for painting



Don't hold back the flight of your fancy!

Segezha Art plywood for painting offers you a vast field for creative experiments.

Now you can create individual, striking and memorable projects without wasting your time preparing the surface for painting.



Striking advantages!



Time savings

Ready for painting. Forget about priming and polishing. No need to waste your time and effort on surface preparation.



Simplicity and reliability

Ideal smooth surface for applying any paint evenly and without cracking.



Durability

Birch plywood is recognized as an exceptionally robust and durable material. A special coating provides additional protection against moisture ingress and deformation, even if the paint is damaged.



Optimized costs

Less paint is consumed. No costs for priming. Reduced costs for subsequent maintenance.



Individual approach

Cutting and CNC based on customized specifications and drawings.



Our products are FSC® certified.

For all occasions where striking solutions are needed!

Segezha Art can be used for both indoor and outdoor applications. Our plywood has been used to create advertising structures and art objects, in interior design, and to produce road signs, children's playgrounds, furniture, interior decorations and vehicles.

With Segezha Art plywood for painting, your possibilities are limited only by your imagination.

The choice is obvious!

ORDINARY PLYWOOD	Segezha Art PLYWOOD
The paint settles unevenly. Multiple layers of paint are required to achieve desirable effect.	A perfectly even surface with high coverage. It is sufficient to paint 1 or 2 layers.
Flaking and cracking of paint is possible.	A special coating eliminates the risk of paint flaking and cracking.
If the paint layer is damaged, the plywood gradually deteriorates because the wood is no longer protected against the adverse effect of moisture.	The additional layer of film protects the plywood in the event of damage to the paint layer, including chipping, wearing or scratching.

SPECIFICATIONS

Dimentions	1220 x 2440, 1250 x 2500 mm – 4 x 8
	2440 x 1220, 2500 x 1250 mm – 8 x 4
	1500 x 3000, 1525 x 3050 mm – 5 x 10
	1220/1250 x 3000/3050 mm – 4 x 10
	1500/1525 x 2400/2440/2500 mm – 5 x 8
Thickness	6–40 mm
Texture	Smooth
Colour, coating type, density	Light grey, 200 g/m ² Kraft, 291 g/m ²
Formaldehyde emission class	E1
Glue category	Exterior, WBP



FPC confirmed
according
to EN 13986



www.fsc.org
FSC-C084688



CARB

Manufactured in accordance with the specification TU 16.21.12-006-93222532-2019



manufacturing

two industrial sites



team

professional excellence
and commitment
of the team



quality

state-of-the-art
equipment,
systems of
ultrasound and
optical scanning



certification

over **95%** of our forest
land has been certified
according to the FSC®
Standard



service

customized approach to each order;
we offer cutting and CNC processing
services based on the customer's
specifications; worldwide delivery



resources

we have our own sources
of raw materials

we planted
12000 km²
of forest
within
just **5** years



OFFICE IN MOSCOW:

18/9, Andropova pr.,
RU-115432 Moscow, Russia
Phone: +7 499 962 82 00

VYATSKY PLYWOOD MILL LLC

KIROVSKY PLYWOOD MILL LLC

1, Commune street, Kirov
Kirov region, 610013, Russia